

## Thermal Carrying Capacity for Bambi Buckets

| Bambi Bucket | Capacity |        | Water Weight |        | Thermal Capacity |       |
|--------------|----------|--------|--------------|--------|------------------|-------|
|              | USG      | Liters | Lbs          | Kg     | BTU              | Kw    |
| BB6072       | 72       | 272.5  | 600          | 272.4  | 674,339          | 198   |
| BB8096       | 96       | 363.4  | 801          | 363.2  | 899,119          | 263   |
| BB9011       | 108      | 408.8  | 901          | 408.6  | 1,011,509        | 296   |
| BB1012       | 122      | 461.8  | 1,017        | 461.5  | 1,142,630        | 335   |
| BB1214       | 144      | 545.1  | 1,201        | 544.8  | 1,348,678        | 395   |
| BB1518       | 180      | 681.4  | 1,501        | 680.9  | 1,685,848        | 494   |
| BB1821       | 216      | 817.6  | 1,801        | 817.1  | 2,023,017        | 593   |
| BB2024       | 240      | 908.5  | 2,002        | 907.9  | 2,247,797        | 659   |
| BB2226       | 260      | 984.2  | 2,168        | 983.6  | 2,435,113        | 713   |
| BB2732       | 320      | 1211.3 | 2,669        | 1210.6 | 2,997,062        | 878   |
| BB3137       | 370      | 1400.6 | 3,086        | 1399.7 | 3,465,353        | 1,015 |
| BB3542       | 420      | 1589.9 | 3,503        | 1588.9 | 3,933,644        | 1,153 |
| BB4453       | 530      | 2006.3 | 4,420        | 2005.0 | 4,963,885        | 1,454 |
| BB5566       | 660      | 2498.4 | 5,504        | 2496.8 | 6,181,441        | 1,811 |
| BB680K       | 680      | 2574.1 | 5,671        | 2572.5 | 6,368,758        | 1,866 |
| BB6578       | 780      | 2952.6 | 6,505        | 2950.8 | 7,305,340        | 2,140 |
| BB7590       | 900      | 3406.9 | 7,506        | 3404.7 | 8,429,238        | 2,470 |
| BBHL4000     | 1,060    | 4012.5 | 8,840        | 4010.0 | 9,927,769        | 2,909 |
| BBHL5000     | 1,320    | 4996.7 | 11,009       | 4993.6 | 12,362,882       | 3,622 |
| BBHL7600     | 2,010    | 7608.7 | 16,763       | 7603.9 | 18,825,298       | 5,516 |
| BBHL9800     | 2,590    | 9804.2 | 21,601       | 9798.0 | 24,257,474       | 7,107 |

Thermal Capacity calculated for 5,000 f (1,524m) , 50° f (10° C)

